

Quantification of Lateral Flow Assays for Test Cassettes with multiple Test Strips

Flexible

- · Can be adapted to almost any rapid test
- For multiple test strips
- For multiplex test cassettes

Precise

- · Can quantify multiple different test lines
- Small CV for interoperability and repeatability

Versatile

- Detachable printer
- · Customizable user interface
- USB and HIS/LIS connectivity
- Mobile data management



Accessories and software









Product Information

Application: Quantification, semiquantification or qualification of

test line intensity; adaptable for multiple test lines

Test Format: Test cassettes with multiple test strips

User: Professional staff, mobile and clinical usage Dimensions: 210 mm x 170 mm x 50/70 mm (L x W x H) Dimensions Test Cartridge: Max. 80 mm x 80 mm x 6 mm (L x W x H)

Weight: Ca. 1100 g

Display: 4.3" TFT graphic display

Keypad: 10 numeric keys, 5 function keys Measuring Time: Approx. 15 sec/ measurement

(each teststrip = 1 measurement)

Calibration Card: SD card

Memory: Integrated flash-ROM

Memory Capacity: > 1000 patient data files

Interface: USB port, D-sub socket (for printer), SD card slot,

connection to hospital information systems (HIS)

via HL7 possible

Battery Life: 8 hours

Language Options: English, German, Spanish, French, Italian, upgrade to

further languages possible

Timer Function: Adjustable upon calibration; default setting 15 min.

Barcode Reader: Integrated for test recognition (barcode label on test

cartridge backside), external for patient/operator

recognition via barcode

Operation Temperature: 10°C ... 35°C
Operation Humidity (rel.): 20 ... 85%

Storage Temperature: -30°C ... 80°C

Degree of Protection: IP 20

Power Supply: Lithium ion battery (rechargeable), AC/DC converter

100-240 V; 47-63 Hz

External Thermal Printer: Optional

Package Contents: Case with accessories

Certified according to ISO 13485:2016

For More Information

Visit: www.chembiogermany.de Call: +49 (0)30. 639 220 32 Email: CDGinfo@chembio.com

